



Advertising screen (24") for independent management of advertising content

Operation via intuitive 10" screen integrated with RFID

Comfortable screen visibility with day/night mode

Different variants of terminals and payment operators

Four-side service access

Cable Management System (CMS) with flat arm and braking mechanism

LED lighting to indicate the occupied status of the charging point (wide visibility)

Panel illumination and functional lightning integrated, indicating charging level status (SOC)

High efficiency of ventilation system while maintaining low noise emissions < 60 dBA

AC Socket

Weatherproof and vandal resistant housing -35°C+55°C

+ Comfort of use for people with limited mobility

+ Remote diagnostics and software updates

POWER SPLIT

Axon Easy 60 kW	Axon Easy 90 kW	Axon Easy 120 kW	Axon Easy 150 kW	Axon Easy 180 kW
1 x 60 kW / AC	1 x 90 kW / AC	1 x 120 kW / AC	1 x 150 kW / AC	1 x 180 kW / AC
2 x 30 kW / AC		2 x 60 kW / AC		2 x 90 kW / AC

AC - AC Socket

SELECT OPTIONS TO DESIGN YOUR PERFECT AXON EASY



Branding (Mini, Midi, Maxi, Full Wrap)



Connector extension (DC uncooled up to 7 or 9.5m)



Payment terminals and operators (Pax IM30, Payter Apollo, Valina, Ingenico 2000)



Meters (Standard, Eichrecht, MID)



AD Display (individual or public advertising use)



Power upgrade (60 > 120, 180 kW, 120 > 180 kW)



AC Socket



AXON EASY 180



EV



E-VAN



E-BUS



E-TRUCK

DC charging station suitable for all electric vehicles, for fast and friendly charging. This versatile and innovative device is designed to integrate with all charging service providers. The charging station is of modular design so its power can be increased even after installation. It will work in all weather conditions, is easy to install and operate, and is a perfect solution in many demanding locations. Device is equipped with a range of comfortable and helpful innovations that make car charging easier, smarter and more intuitive.



Expressways



Parkings



Charging stations



Airports



City centers



Commercial spaces

Power	60, 90, 120, 150, 180 kW
Device type	All In One Charging Station
Power upgrade	60 >120 60 >180 120 >180
Connectors	60, 120, 180 kW - CCS CCS 90, 150 kW - CCS 180 kW - CCS HPC / CCS HPC
Max. charging current	60, 90, 120 kW - 250 A 150, 180 kW - 400 A (to 500) 180 kW (CCS HPC ver.) - 500 A
Voltage range	150 – 1000 V
Selection of options	DC Meters AC Socket AD Display Branding Cables lenght Payment terminals
Metering standard	Eichrecht, MID compliant
Plug & Charge	ready

POWER THAT
MOVES YOU

ekoenergetyka.com

Find out more



PHOTOMATE
OFFICIAL DISTRIBUTOR

photomate.eu